

Crimping Machines

NK16 1" Crimper

Application
2-SN 1"
4-SP ½"



Crimp Force	80 Tons
Max Crimp Size	1 Inch (25mm)
Max Die Length	56 mm
Opening w/out Dies	118mm
Gross Weight	62 lbs (28kgs)
Dimensions	12" x 9" x 16"
Control	Hand Pump
Applicable Die Sets	16 Series

K40 2" Crimper

Application
2" four wire
2" Industrial



Crimp Force	240 Tons
Max Crimp Size	3 inch (76 mm)*
Max Die Length	4 inch (100mm)
Opening w/out Dies	4.6 inch (118 mm)
Gross Weight	400 lbs (180 kgs)
Motor	5 Hp (4 kW) - 208/480V 3ph
Voltage Options	230V 1 Ph
Dimensions	24" x 16" x 25"
Control	Touch Screen or Micrometer
Applicable Die Sets	40 Series

KP300 Production Crimper

Application
2" six wire Hydraulic
6" Industrial



Crimp Force	300 Tons
Max Crimp Size	6 inch (300mm)
Max Die Length	5 inch (125mm)
Opening w/ Dies	+3.25 inch (80 mm)
Opening w/out Dies	8.8 inch (225mm)
Gross Weight	2000 lbs.
Motor	7.5 Hp (5.5kW) -208/480V 3Ph
Voltage Options	230V 3Ph or 480V 3 Ph
Dimensions	31" x 31" x 60"
Control	Touch Screen
Applicable Die Sets	60 & 60L Series

Products and Materials:



3" 90° Hydraulic Elbow Fitting



ANSI 150 lb. Flange



Cam and Groove

Die Sets:

(Adapters are 130/80, 230/80, 145/80)

- 16 Series - 10, 12, 15, 18, 21, 24, 27, 30
- 40 Series - 10, 12, 15, 18, 21, 24, 27, 30, 33, 39, 45, 51, 57, 66, 70
- 60 Series - 10, 12, 15, 18, 21, 24, 27, 30, 33, 39, 45, 51, 57, 66
- 60L Series - 73, 80, 86, 90, 95, 99, 112, 117, 122
- 285 Series - 136, 146, 156, 166, 176, 186, 196, 206, 215